



NOTE: ALL STATION AND OFFSETS ARE TAKEN FROM THE CENTERLINE OF CONSTRUCTION UNLESS OTHERWISE NOTED  
ALL DIMENSIONS ARE TO THE EDGE OF PAVEMENT UNLESS OTHERWISE NOTED

SLOPES AS FOLLOWS:	
△	SLOPE 6% OR RATE OF S.E. WHICHEVER IS GREATER
□	S.E. RATE OF 2%, USE 6% S.E. RATE OF 3%, USE 5% S.E. RATE OF 4%, USE 4% S.E. RATE OF 5%, USE 3% S.E. RATE OF 6%, USE 2%

ALGEBRAIC DIFFERENCE IN SLOPES NOT TO EXCEED 8%

- REQUIRED PAVEMENT**
- Ⓐ 165 LB/SQ YD - 1.5" ASPH. CONC. 12.5mm SUPERPAVE
  - Ⓑ 220 LB/SQ YD - 2" ASPH. CONC. 19 mm SUPERPAVE
  - Ⓒ 330 LB/SQ YD - 3" ASPH. CONC. 25 mm SUPERPAVE
  - Ⓓ 660 LB/SQ YD - 6" ASPH. CONC. 25 mm SUPERPAVE
  - Ⓔ 12" GRADED AGGREGATE BASE
  - Ⓕ ASPHALT LEVELING AS REQUIRED
  - Ⓖ 8 IN X 30 IN CONC. CURB & GUTTER TP. 2
  - Ⓙ CONCRETE INTEGRAL MEDIAN, 7.5"
  - Ⓚ 6" CONCRETE HEADER CURB, TYPE 7
  - Ⓛ 4" CONCRETE HEADER CURB, TYPE 9